



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/816,623	04/02/2004	Scott B. Peterson	590282001700	1063
25226	7590	05/18/2006	EXAMINER	
MORRISON & FOERSTER LLP			BROOME, SAID A	
755 PAGE MILL RD			ART UNIT	
PALO ALTO, CA 94304-1018			PAPER NUMBER	
			2628	

DATE MAILED: 05/18/2006

Please find below and/or attached an Office communication concerning this application or proceeding.

Office Action Summary	Application No. 10/816,623	Applicant(s) PETERSON, SCOTT B.	
	Examiner Said Broome	Art Unit 2628	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 02 April 2004.
- 2a) ☐ This action is **FINAL**. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 1-92 is/are pending in the application.
- 4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) ☒ Claim(s) 21-30, 32-39 and 57-78 is/are allowed.
- 6) ☒ Claim(s) 1, 2, 40, 79, 84 and 88-91 is/are rejected.
- 7) ☒ Claim(s) 3-20, 31, 41-56, 80-83, 85-87 and 92 is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on _____ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☐ Some * c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
2. ☐ Certified copies of the priority documents have been received in Application No. _____.
3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).
- * See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- | | |
|--|---|
| 1) <input checked="" type="checkbox"/> Notice of References Cited (PTO-892) | 4) <input type="checkbox"/> Interview Summary (PTO-413)
Paper No(s)/Mail Date. _____ |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948) | 5) <input type="checkbox"/> Notice of Informal Patent Application (PTO-152) |
| 3) <input checked="" type="checkbox"/> Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08)
Paper No(s)/Mail Date <u>10/04</u> | 6) <input type="checkbox"/> Other: _____ |

DETAILED ACTION

Claim Rejections - 35 USC § 103

The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

Claims 1, 2 and 79 are rejected under 35 U.S.C. 103(a) as being unpatentable over Touma et al. (US Patent 6,167,159) in view of Lee et al. ("Vertex Data Compression For Triangular Meshes").

Regarding claim 1, Touma et al. teaches all the limitations except using a basis coordinate system respectively associated with the reference vertices. Touma et al. teaches a method for compressing an animation model in column 1 lines 65-67 ("...compact storage of 3D objects."), the model comprising an offset model including a plurality of surfaces, each surface including a plurality of vertices in column 3 lines 58-63 ("the vertex coordinates are represented by an offset between a prediction of the coordinates and the actual coordinates."), column 6 lines 40-50 ("...to generate a compressed coordinate list in which the coordinates of at least some of the vertices are represented as an offset from a predicted value...") and in column 11 lines 16-17 ("...outputting the list includes rendering the mesh."), where it is described that the offset or difference between the vertices of contained on the mesh surface the model is rendered when the list of offset values is generated. Touma et al. also teaches predicting offset vertices of the offset model or mesh for corresponding reference vertices of a reference model associated with the offset model in column 6 lines 40-50 ("...compressing a mesh including a plurality of vertices

Art Unit: 2628

having geometric coordinates, including arranging the vertices in a consecutive order, compressing the coordinates so as to generate a compressed coordinate list in which the coordinates of at least one of the vertices are represented as an offset from a predicted value, which is calculated based on the coordinates of a plurality of the preceding vertices in the consecutive order...“). Touma et al. also teaches determining a difference between the predicted offset vertices and actual offset vertices of the offset model in column 3 lines 61-63 (“...vertex coordinates are represented by an offset between a prediction of the coordinates and the actual coordinates.”). Touma et al. also teaches storing the differences between the predicted offset vertices and actual offset vertices in column 8 lines 1-13 (“...a method for decompressing a compressed stream of signals into a mesh... including extracting a coordinate list from the stream...extracting from the coordinate list at least one value representing an offset from an actual coordinate of one of the vertices to a predicted coordinate thereof, calculating the predicted value of the vertex coordinate, and subtracting the offset from the predicted value to obtain the actual coordinate...” and column 7 lines 13-14 (“...storing the stream of signals in a memory.”), where it is described that the signals containing the differences between the predicted values and actual values are stored in memory. Touma et al. also teaches reconstruction or rendering of the actual offset vertices using the reference vertices and the differences in column 10 lines 1-8 (“...a stream of signals into a mesh including a plurality of vertices...representing the degrees of the vertices in a consecutive order, from the stream, and which generates and renders the mesh...”), where it is described that the rendering is performed based on streams of information regarding the difference between the offset and actual vertices as described in column 8 lines 1-13 (“...a method for decompressing a compressed stream of

signals into a mesh... including extracting a coordinate list from the stream...calculating the predicted value of the vertex coordinate, and subtracting the offset from the predicted value to obtain the actual coordinate...”). Again, Touma et al. fails to teach using a basis coordinate system respectively associated with the reference vertices. Lee et al. teaches using a basis coordinate system respective to the reference, or previous processed, vertices on page 1 first column paragraph one lines 6-7 (“...a coordinate system formed by the three previously processed vertices.”), which basis coordinate system formed for all the vertices as described on page lines (“we transform all the vertices...by the previously processed triangle...”). It would have been obvious to one of ordinary skill in the art to combine the teachings of Touma et al. with Lee et al. because this combination would provide efficient reduction of data used to represent three-dimensional objects through storage of compression of the data.

Regarding claim 2, Touma et al. fails to teach the limitations. Lee et al. teaches a basis coordinate system that comprises a set of vertices that are vertices previously traversed on page 1 first column paragraph one lines 6-7 (“...a coordinate system formed by the three previously processed vertices.”). The motivation to combine the teachings of Touma et al. and Lee et al. is equivalent to the motivation of claim 1.

Regarding claim 79, Touma et al. teaches all the limitations except using a basis coordinate system respectively associated with the reference vertices. Touma et al. teaches a system for compressing an animation model in column 12 lines 49-63 (“FIG. 1 is a schematic illustration of a system 18 for transmission of a three-dimensional mesh object 22...Object 22 is then compressed using a software program...”), the model comprising an offset model including a plurality of surfaces, each surface including a plurality of vertices in column 3 lines 58-63 (“the

vertex coordinates are represented by an offset between a prediction of the coordinates and the actual coordinates.”), column 6 lines 40-50 (“...to generate a compressed coordinate list in which the coordinates of at least some of the vertices are represented as an offset from a predicted value...” and in column 11 lines 16-17 (“...outputting the list includes rendering the mesh.”), where it is described that the offset or difference between the vertices of contained on the mesh surface the model is rendered when the list of offset values is generated. . Touma et al. also teaches predicting offset vertices of the offset model or mesh for corresponding reference vertices of a reference model associated with the offset model in column 6 lines 40-50 (“...compressing a mesh including a plurality of vertices having geometric coordinates, including arranging the vertices in a consecutive order, compressing the coordinates so as to generate a compressed coordinate list in which the coordinates of at least one of the vertices are represented as an offset from a predicted value, which is calculated based on the coordinates of a plurality of the preceding vertices in the consecutive order...”). Touma et al. also teaches determining a difference between the predicted offset vertices and actual offset vertices of the offset model in column 3 lines 61-63 (“...vertex coordinates are represented by an offset between a prediction of the coordinates and the actual coordinates.”). Touma et al. also teaches storing the differences between the predicted offset vertices and actual offset vertices in column 8 lines 1-13 (“...a method for decompressing a compressed stream of signals into a mesh... including extracting a coordinate list from the stream...extracting from the coordinate list at least one value representing an offset from an actual coordinate of one of the vertices to a predicted coordinate thereof, calculating the predicted value of the vertex coordinate, and subtracting the offset from the predicted value to obtain the actual coordinate...”) and column 7 lines 13-14

Art Unit: 2628

(“...storing the stream of signals in a memory.”), where it is described that the signals containing the differences between the predicted values and actual values are stored in memory. Touma et al. also teaches reconstruction or rendering of the actual offset vertices using the reference vertices and the differences in column 10 lines 1-8 (“...a stream of signals into a mesh including a plurality of vertices...representing the degrees of the vertices in a consecutive order, from the stream, and which generates and renders the mesh...”), where it is described that the rendering is performed based on streams of information regarding the difference between the offset and actual vertices as described in column 8 lines 1-13 (“...a method for decompressing a compressed stream of signals into a mesh... including extracting a coordinate list from the stream...calculating the predicted value of the vertex coordinate, and subtracting the offset from the predicted value to obtain the actual coordinate...”). Again, Touma et al. fails to teach using a basis coordinate system respectively associated with the reference vertices. Lee et al. teaches using a basis coordinate system respective to the reference, or previous processed, vertices on page 1 first column paragraph one lines 6-7 (“...a coordinate system formed by the three previously processed vertices.”), which basis coordinate system formed for all the vertices as described on page lines (“we transform all the vertices...by the previously processed triangle...”). The motivation to combine the teachings of Touma et al. and Lee et al. is equivalent to the motivation of claim 1.

Claims 40, 84, 88, 90 and 91 are rejected under 35 U.S.C. 103(a) as being unpatentable over Touma et al. in view of Lee et al. in further view of Mack (US 6,831,637).

Regarding claim 40, Touma et al. teaches all the limitations except using a basis coordinate system and combining the predicted offset vertices and the stored differences to produce the offset vertices of the offset model. Touma et al. teaches a method for decompressing a compressed animation model, in column 7 lines 18-26 (“...a method for decompressing a compressed stream of signals into a mesh having a plurality of vertices having geometric coordinates...”), the model representing an offset model including a plurality of surfaces, each surface including a plurality of vertices in column 3 lines 58-63 (“the vertex coordinates are represented by an offset between a prediction of the coordinates and the actual coordinates.”), column 6 lines 40-50 (“...to generate a compressed coordinate list in which the coordinates of at least some of the vertices are represented as an offset from a predicted value...”) and in column 11 lines 16-17 (“...outputting the list includes rendering the mesh.”), where it is described that the offset or difference between the vertices of contained on the mesh surface the model is rendered when the list of offset values is generated. Touma et al. also teaches determining a difference between the predicted offset vertices and actual offset vertices of the offset model in column 3 lines 61-63 (“...vertex coordinates are represented by an offset between a prediction of the coordinates and the actual coordinates.”). Touma et al. also teaches storing the differences between the predicted offset vertices and actual offset vertices in column 8 lines 1-13 (“...a method for decompressing a compressed stream of signals into a mesh...including extracting a coordinate list from the stream...extracting from the coordinate list at least one value representing an offset from an actual coordinate of one of the vertices to a predicted coordinate

Art Unit: 2628

thereof, calculating the predicted value of the vertex coordinate, and subtracting the offset from the predicted value to obtain the actual coordinate...” and column 7 lines 13-14 (“...storing the stream of signals in a memory.”), therefore one of ordinary skill in the art would be capable of retrieving the stored difference data because the signals containing the differences between the predicted values and actual values are stored in memory. Again, Touma et al. fails to teach using a basis coordinate system respectively associated with the reference vertices and combining the predicted offset vertices and the stored differences to produce the offset vertices of the offset model. Lee et al. teaches using a basis coordinate system respective to the reference, or previous processed, vertices on page 1 first column paragraph one lines 6-7 (“...a coordinate system formed by the three previously processed vertices.”), which basis coordinate system formed for all the vertices as described on page lines (“we transform all the vertices...by the previously processed triangle...”). Touma et al. and Lee et al. fail to teach combining the predicted offset vertices and the stored differences to produce the offset vertices of the offset model. Mack teaches combining the predicted offset vertices and the stored differences to produce the offset vertices of the offset model in column 4 lines 13-16 (“Assuming that vertex 2 is (5.5, 20, 26), compression machine 100 then subtracts vertex 2 from vertex 1 using combination unit 118 to generate (0.5, 1, 0.5) which is stored.”) and column 4 lines 41-46 (“Predictor 502 receives coordinates (0.5, 0, 1), and adds the coordinates to vertex 1 to generate vertex 2 (5.5, 20, 26).”). It would have been obvious to one of ordinary skill in the art to combine the teachings of Touma et al., Lee et al. and Mack because this combination would provide efficient reduction of data used to represent three-dimensional objects through storage of compressed differences between predicted and actual vertices.

Regarding claim 84, Touma et al. teaches all the limitations except using a basis coordinate system respectively associated with the reference vertices. Touma et al. teaches a system for decompressing an animation model in column 10 lines 38-41 (“...apparatus for decompressing a compressed stream of signals into a mesh having a plurality of vertices having geometric coordinates...”), the model comprising an offset model including a plurality of surfaces, each surface including a plurality of vertices in column 3 lines 58-63 (“the vertex coordinates are represented by an offset between a prediction of the coordinates and the actual coordinates.”), column 6 lines 40-50 (“...to generate a compressed coordinate list in which the coordinates of at least some of the vertices are represented as an offset from a predicted value...”), and in column 11 lines 16-17 (“...outputting the list includes rendering the mesh.”), where it is described that the offset or difference between the vertices of contained on the mesh surface the model is rendered when the list of offset values is generated. . Touma et al. also teaches predicting offset vertices of the offset model or mesh for corresponding reference vertices of a reference model associated with the offset model in column 6 lines 40-50 (“...compressing a mesh including a plurality of vertices having geometric coordinates, including arranging the vertices in a consecutive order, compressing the coordinates so as to generate a compressed coordinate list in which the coordinates of at least one of the vertices are represented as an offset from a predicted value, which is calculated based on the coordinates of a plurality of the preceding vertices in the consecutive order...”). Touma et al. also teaches determining a difference between the predicted offset vertices and actual offset vertices of the offset model in column 3 lines 61-63 (“...vertex coordinates are represented by an offset between a prediction of the coordinates and the actual coordinates.”). Touma et al. also teaches

storing the differences between the predicted offset vertices and actual offset vertices in column 8 lines 1-13 (“...a method for decompressing a compressed stream of signals into a mesh... including extracting a coordinate list from the stream...extracting from the coordinate list at least one value representing an offset from an actual coordinate of one of the vertices to a predicted coordinate thereof, calculating the predicted value of the vertex coordinate, and subtracting the offset from the predicted value to obtain the actual coordinate...”)) and column 7 lines 13-14 (“...storing the stream of signals in a memory.”), where it is described that the signals containing the differences between the predicted values and actual values are stored in memory. Touma et al. also teaches reconstruction or rendering of the actual offset vertices using the reference vertices and the differences in column 10 lines 1-8 (“...a stream of signals into a mesh including a plurality of vertices...representing the degrees of the vertices in a consecutive order, from the stream, and which generates and renders the mesh...”)), where it is described that the rendering is performed based on streams of information regarding the difference between the offset and actual vertices as described in column 8 lines 1-13 (“...a method for decompressing a compressed stream of signals into a mesh... including extracting a coordinate list from the stream...calculating the predicted value of the vertex coordinate, and subtracting the offset from the predicted value to obtain the actual coordinate...”)). Again, Touma et al. fails to teach using a basis coordinate system respectively associated with the reference vertices. Lee et al. teaches using a basis coordinate system respective to the reference, or previous processed, vertices on page 1 first column paragraph one lines 6-7 (“...a coordinate system formed by the three previously processed vertices.”)), which basis coordinate system formed for all the vertices as described on page lines (“we transform all the vertices...by the previously processed

triangle...”). The motivation to combine the teachings of Touma et al., Lee et al. and Mack is equivalent to the motivation of claim 40.

Regarding claim 88, Touma et al. teaches all the limitations except using a basis coordinate system respectively associated with the reference vertices and combining the predicted offset vertices and the stored differences to produce the offset vertices of the offset model. Touma et al. teaches a method for compressing, in column 1 lines 65-67 (“...compact storage of 3D objects.”), and decompressing, in column 10 lines 38-41 (“...apparatus for decompressing a compressed stream of signals into a mesh having a plurality of vertices having geometric coordinates...”), an animation model, the model comprising an offset model including a plurality of surfaces, each surface including a plurality of vertices in column 3 lines 58-63 (“the vertex coordinates are represented by an offset between a prediction of the coordinates and the actual coordinates.”), column 6 lines 40-50 (“...to generate a compressed coordinate list in which the coordinates of at least some of the vertices are represented as an offset from a predicted value...”), and in column 11 lines 16-17 (“...outputting the list includes rendering the mesh.”), where it is described that the offset or difference between the vertices of contained on the mesh surface the model is rendered when the list of offset values is generated. Touma et al. also teaches predicting offset vertices of the offset model or mesh for corresponding reference vertices of a reference model associated with the offset model in column 6 lines 40-50 (“...compressing a mesh including a plurality of vertices having geometric coordinates, including arranging the vertices in a consecutive order, compressing the coordinates so as to generate a compressed coordinate list in which the coordinates of at least one of the vertices are represented as an offset from a predicted value, which is calculated based on the coordinates of a

plurality of the preceding vertices in the consecutive order...“). Touma et al. also teaches determining a difference between the predicted offset vertices and actual offset vertices of the offset model in column 3 lines 61-63 (“...vertex coordinates are represented by an offset between a prediction of the coordinates and the actual coordinates.“). Touma et al. also teaches storing the differences between the predicted offset vertices and actual offset vertices in column 8 lines 1-13 (“...a method for decompressing a compressed stream of signals into a mesh... including extracting a coordinate list from the stream...extracting from the coordinate list at least one value representing an offset from an actual coordinate of one of the vertices to a predicted coordinate thereof, calculating the predicted value of the vertex coordinate, and subtracting the offset from the predicted value to obtain the actual coordinate...””) and column 7 lines 13-14 (“...storing the stream of signals in a memory.“), therefore one of ordinary skill in the art would be capable of retrieving the stored difference data because the signals containing the differences between the predicted values and actual values are stored in memory. Touma et al. also teaches reconstruction or rendering of the actual offset vertices using the reference vertices and the differences in column 10 lines 1-8 (“...a stream of signals into a mesh including a plurality of vertices...representing the degrees of the vertices in a consecutive order, from the stream, and which generates and renders the mesh...“), where it is described that the rendering is performed based on streams of information regarding the difference between the offset and actual vertices as described in column 8 lines 1-13 (“...a method for decompressing a compressed stream of signals into a mesh... including extracting a coordinate list from the stream...calculating the predicted value of the vertex coordinate, and subtracting the offset from the predicted value to obtain the actual coordinate...””). Again, Touma et al. fails to teach using a basis coordinate

Art Unit: 2628

system respectively associated with the reference vertices and combining the predicted offset vertices and the stored differences to produce the offset vertices of the offset model. Lee et al. teaches using a basis coordinate system respective to the reference, or previous processed, vertices on page 1 first column paragraph one lines 6-7 (“...a coordinate system formed by the three previously processed vertices.”), which basis coordinate system formed for all the vertices as described on page lines (“we transform all the vertices...by the previously processed triangle...”). Touma et al. and Lee et al. fail to teach combining the predicted offset vertices and the stored differences to produce the offset vertices of the offset model. Mack teaches combining the predicted offset vertices and the stored differences to produce the offset vertices of the offset model in column 4 lines 13-16 (“Assuming that vertex 2 is (5.5, 20, 26), compression machine 100 then subtracts vertex 2 from vertex 1 using combination unit 118 to generate (0.5, 1, 0.5) which is stored.”) and column 4 lines 41-46 (“Predictor 502 receives coordinates (0.5, 0, 1), and adds the coordinates to vertex 1 to generate vertex 2 (5.5, 20, 26).”). The motivation to combine the teachings of Touma et al., Lee et al. and Mack is equivalent to the motivation of claim 40.

Regarding claim 90, Touma et al. teaches a method for decompressing an animation model in column 10 lines 38-41 (“...apparatus for decompressing a compressed stream of signals into a mesh having a plurality of vertices having geometric coordinates...”), the model comprising an offset model including a plurality of surfaces, each surface including a plurality of vertices in column 3 lines 58-63 (“the vertex coordinates are represented by an offset between a prediction of the coordinates and the actual coordinates.”), column 6 lines 40-50 (“...to generate a compressed coordinate list in which the coordinates of at least some of the vertices are

Art Unit: 2628

represented as an offset from a predicted value...”) and in column 11 lines 16-17 (“...outputting the list includes rendering the mesh.”), where it is described that the offset or difference between the vertices of contained on the mesh surface the model is rendered when the list of offset values is generated. Touma et al. also teaches storing a compressed representation of the a surface of an offset model in column 8 lines 1-13 (“...a method for decompressing a compressed stream of signals into a mesh...including extracting a coordinate list from the stream...extracting from the coordinate list at least one value representing an offset from an actual coordinate of one of the vertices to a predicted coordinate thereof, calculating the predicted value of the vertex coordinate, and subtracting the offset from the predicted value to obtain the actual coordinate...””) and column 7 lines 13-14 (“...storing the stream of signals in a memory.”), therefore one of ordinary skill in the art would be capable of retrieving the stored difference data because the signals containing the differences between the predicted values and actual values are stored in memory. Touma et al. fails to teach decompressing the compressed geometric representation with respect to the reference model at the second time, or actual vertice, to produce the offset model at the first time, or predicted vertice. Mack teaches decompressing the compressed geometric representation with respect to the reference model at the second time, or actual vertice, to produce the offset model at the first time, or predicted vertice in column 4 lines 39-42 (“Decompression 504 retrieves the coordinates from the compressed list and stores it in data unit 508. Predictor 502 receives coordinates (0.5, 0, 1), and adds the coordinates to vertex 1 to generate vertex 2 (5.5, 20, 26).”). The motivation to combine the teachings of Touma et al., Lee et al. and Mack is equivalent to the motivation of claim 40.

Regarding claim 91, Touma et al. teaches a system for providing a compressed animation model for an animation cycle in column 6 lines 40-50 (“...including arranging the vertices in a consecutive order, compressing the coordinates so as to generate a compressed coordinate list in which the coordinates of at least one of the vertices are represented as an offset from a predicted value...”)) where it is described that the vertices of a 3D object are compressed in a consecutive order, therefore the object would be capable of compression in an animation cycle for a plurality of frames of animation. Touma et al. teaches a reference model comprising a geometric representation describing that surface of the model for a first frame of animation cycle in column 6 lines 40-50 (“...including arranging the vertices in a consecutive order, compressing the coordinates so as to generate a compressed coordinate list in which the coordinates of at least one of the vertices are represented as an offset from a predicted value, which is calculated based on the coordinates of a plurality of the preceding vertices in the consecutive order...”)) where it is described that the predicted and actual vertices are represented in consecutive order, and it is also described in column 12 lines 57-60 (“Object 22 is preferably generated in accordance with the VRML standard or is translated into the VRML standard, using computer programs known in the art...”)), that the objects are compatible with VRML files that are known in the art to comprise animation 3D models. Touma et al. also teaches a plurality of compressed, offset animation models, each compressed offset animation model corresponding to a subsequent or consecutive frame of the animation cycle, and comprising a compressed geometric representation of a surface of the offset model corresponding to the reference vertices in column 1 lines 65-67 (“...compact storage of 3D objects.”) and in column 6 lines 40-50 (“...arranging the vertices in a consecutive order, compressing the coordinates so as to generate a compressed coordinate list in which the

coordinates of at least one of the vertices are represented as an offset from a predicted value, which is calculated based on the coordinates of a plurality of the preceding vertices in the consecutive order...”).

Claim Rejections - 35 USC § 102

The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless –

(b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.

Claim 89 is rejected under 35 U.S.C. 102(b) as being anticipated by Touma et al.(US Patent 6,167,159).

Regarding claim 89, Touma et al. teaches a method for compressing an animation model in column 1 lines 61-64 (“...present invention to provide apparatus and methods of compression to allow fast transfer of three dimensional (3D) objects...”), the model comprising an offset model including a plurality of surfaces, each surface including a plurality of vertices in column 3 lines 58-63 (“the vertex coordinates are represented by an offset between a prediction of the coordinates and the actual coordinates.”), column 6 lines 40-50 (“...to generate a compressed coordinate list in which the coordinates of at least some of the vertices are represented as an offset from a predicted value...” and in column 11 lines 16-17 (“...outputting the list includes rendering the mesh.”), where it is described that the offset or difference between the vertices of contained on the mesh surface the model is rendered when the list of offset values is generated.

Touma et al. teaches compressing the animation model by compressing a geometric representation of the surface of the offset model at a first time, or predicted vertice, with respect to a reference model at a second time earlier than the first time, or actual vertice, in column 3 lines 58-65 (“...the vertex coordinates are represented by an offset between a prediction of the coordinates and the actual coordinates. Preferably, the prediction is based on more than one other vertex appearing earlier in the consecutive order...”). Touma et al. also teaches storing the compressed representation in column 8 lines 1-13 (“...a method for decompressing a compressed stream of signals into a mesh... including extracting a coordinate list from the stream...extracting from the coordinate list at least one value representing an offset from an actual coordinate of one of the vertices to a predicted coordinate thereof, calculating the predicted value of the vertex coordinate, and subtracting the offset from the predicted value to obtain the actual coordinate...”) and column 7 lines 13-14 (“...storing the stream of signals in a memory.”), where it is described that the signals containing the differences between the predicted values and actual values are stored in memory.

Allowable Subject Matter

Claims 21-30, 32-39 and 57-78 are allowed.

The following is an examiner’s statement of reasons for allowance:

The prior art, Touma et al., Lee et al. and Mack do not teach all the limitations of claim 21. Touma et al. teaches determining offset vertices of a 3D model and determining the difference between the predicted offset vertex and the actual offset vertex in column 3 lines 61-63 (“...vertex coordinates are represented by an offset between a prediction of the coordinates

Art Unit: 2628

and the actual coordinates.”). Touma et al. also teaches storing the differences between the predicted offset vertices and actual offset vertices in column 8 lines 1-13 (“...a method for decompressing a compressed stream of signals into a mesh...extracting a coordinate list from the stream...extracting from the coordinate list at least one value representing an offset from an actual coordinate of one of the vertices to a predicted coordinate thereof, calculating the predicted value of the vertex coordinate, and subtracting the offset from the predicted value to obtain the actual coordinate...””) and column 7 lines 13-14 (“...storing the stream of signals in a memory.”), where it is described that the signals containing the differences between the predicted values and actual values are stored in memory. However, none of the cited prior art teaches traversing a plurality of reference vertices on a surface of the reference model associated with the offset model, and for each reference vertex: selecting an offset vertex of the offset model corresponding to the reference vertex, selecting a basis coordinate system on the reference model with respect to the reference vertex, the basis coordinate system defined by vertices nearby the reference vertex, the basis coordinate system providing the basis coordinates for the reference vertex, selecting a basis coordinate system on the offset model, determining a position of the reference vertex in the basis coordinate system on the reference model; and predicting the offset vertex by applying the position of the reference vertex in the basis coordinate system on the reference model to the basis coordinate system on the offset model, as recited in claim 21.

The prior art, Touma et al., Lee et al. and Mack do not teach all the limitations of claim 57. Touma et al. teaches determining offset vertices of a 3D model and determining the difference between the predicted offset vertex and the actual offset vertex in column 3 lines 61-63 (“...vertex coordinates are represented by an offset between a prediction of the coordinates

Art Unit: 2628

and the actual coordinates.”). Touma et al. also teaches storing the differences between the predicted offset vertices and actual offset vertices in column 8 lines 1-13 (“...a method for decompressing a compressed stream of signals into a mesh...extracting a coordinate list from the stream...extracting from the coordinate list at least one value representing an offset from an actual coordinate of one of the vertices to a predicted coordinate thereof, calculating the predicted value of the vertex coordinate, and subtracting the offset from the predicted value to obtain the actual coordinate...”) and column 7 lines 13-14 (“...storing the stream of signals in a memory.”), where it is described that the signals containing the differences between the predicted values and actual values are stored in memory. Mack teaches combining the predicted offset vertices and the stored differences to produce the offset vertices of the offset model in column 4 lines 13-16 (“Assuming that vertex 2 is (5.5, 20, 26), compression machine 100 then subtracts vertex 2 from vertex 1 using combination unit 118 to generate (0.5, 1, 0.5) which is stored.”) and column 4 lines 41-46 (“Predictor 502 receives coordinates (0.5, 0, 1), and adds the coordinates to vertex 1 to generate vertex 2 (5.5, 20, 26).”). However, none of the cited prior art teaches traversing a plurality of reference vertices on a surface of the reference model associated with the offset model, and for each reference vertex: selecting an offset vertex of the offset model corresponding to the reference vertex, selecting a basis coordinate system on the reference model with respect to the reference vertex, the basis coordinate system defined by vertices nearby the reference vertex, the basis coordinate system providing the basis coordinates for the reference vertex, selecting a basis coordinate system on the offset model; determining a position of the reference vertex in the basis coordinate system on the reference model; and predicting the

Art Unit: 2628

offset vertex by applying the position of the reference vertex in the basis coordinate system on the reference model to the basis coordinate system on the offset model, as recited in claim 57.

The prior art, Touma et al., Lee et al. and Mack do not teach all the limitations of claim 73. Touma et al. teaches a computer program product, comprising a computer readable medium storing a compressed, offset animation model in column 12 lines 49-67 and column 13 lines 1-5 ("FIG. 1 is a schematic illustration of a system 18 for transmission of a three-dimensional mesh object 22...Object 22 is then compressed using a software program...The compressed form of object 22...is transmitted from server 24 over a network to one or more receiving computers 26 where it may be decompressed, using compatible software, displayed and/or stored."). However, none of the cited prior art teaches a plurality of seed vertices, each seed vertex corresponding to a row of reference vertices on a surface of a reference model associated with the offset model, the seed vertices for predicting a plurality of offset vertices on a surface of the offset model; and a plurality of differences between predicted offset vertices and actual offset vertices, for combining with the plurality of offset vertices predicted from the seed vertices to produce a plurality of final offset vertices on the surface of the offset model.

Continued

Claims 3-20, 31, 41-56, 80-83, 85-87 and 92 are objected to as being dependent upon a rejected base claim, but would be allowable if rewritten in independent form including all of the limitations of the base claim and any intervening claims.

Art Unit: 2628

Any comments considered necessary by applicant must be submitted no later than the payment of the issue fee and, to avoid processing delays, should preferably accompany the issue fee. Such submissions should be clearly labeled "Comments on Statement of Reasons for Allowance."

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Said Broome whose telephone number is (571)272-2931. The examiner can normally be reached on 8:30am-5pm.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Ulka Chauhan can be reached on (571)272-7782. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

S. Broome
5/10/06 *SB*


ULKA CHAUHAN
SUPERVISORY PATENT EXAMINER